




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>B31F 1/07, B41F 15/00, 17/00, 17/08,</b> <b>B41L 13/00, 13/04</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/08865</b> <b>(43) International Publication Date:</b> 25 February 1999 (25.02.99)
<b>(21) International Application Number:</b> PCT/US98/16822 <b>(22) International Filing Date:</b> 13 August 1998 (13.08.98)  <b>(30) Priority Data:</b> 60/055,293 13 August 1997 (13.08.97) US  <b>(71) Applicant (for all designated States except US):</b> FUSION LIGHTING, INC. [US/US]; 7524 Standish Place, Rockville, MD 20855-2730 (US).  <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> LOVE, Wayne, G. [US/US]; 2812 Spartan Road, Olney, MD 20832 (US).  <b>(74) Agents:</b> STEINER, Paul, E.; Fusion Lighting, Inc., 7524 Standish Place, Rockville, MD 20855-2730 (US) et al.		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

**(54) Title:** DIRECT ROTARY SCREEN PRINTING ON CYLINDRICAL ARTICLES

**(57) Abstract**

An apparatus and method for decorating cylindrical articles (122) using direct rotary screen printing of a UV radiation curable composition in various predetermined patterns and registrations. A rotary screen printing assembly (114) is arranged in either a horizontal or vertical orientation to achieve production rates of about at least 250 articles per minute, and up to 1000 articles per minute. The UV radiation curable compositions are at least partially cured between a plurality of screen printing workstations (170, 172) using a UV radiation source (140).

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## DIRECT ROTARY SCREEN PRINTING ON CYLINDRICAL ARTICLES

**BACKGROUND**Field of the Invention

5           The present invention pertains to improvements in high efficacy fill materials within bulbs of discharge lamps and has particular, although not limited, utility in lamps of the type disclosed in U.S. Patent Nos. 5,404,076 and 5,606,220 (Dolan et al.) and PCT Publication WO 92/08240, the disclosures of which are incorporated herein by reference, in their entireties.

10

Related Art

          Electrodeless lamps of the type with which the present invention is concerned are comprised of a light transmissive envelope containing a plasma-forming medium or fill. A microwave or radio frequency (RF) energy source has its output energy  
15   coupled to the envelope via a coupling waveguide to excite a plasma, resulting in a light discharge. In order to initiate breakdown (i.e., ignite the discharge), various techniques have been suggested. For example, in U.S. Patent No. 4,359,668 (Ury), a supplemental ultraviolet igniter bulb, energized by extracting a portion of the primary microwave energy, emits energetic photons incident on the electrodeless lamp  
20   envelope. These photons ionize the fill within the envelope to effect the desired discharge therein.

          Although ignition devices disposed outside the envelope can be effective, they consume space and add to the cost of the overall lamp. Even if an external or supplemental light source is used for starting, starting is not always reliable. It is  
25   desirable, therefore, to incorporate an additive in the fill material that has a low ionization potential and, therefore, facilitates initial breakdown so that the primary fill material can be ignited.

          Other prior art systems used to assist lamp starting employ an arc discharge to free electrons through use of a conductive component to either concentrate a high  
30   strength electric field or introduce a concentrated field from an external power source. However, a system providing concentration or introduction of a high strength electric field requires additional components, thereby increasing cost.

Another approach involves the use of a fill additive which is partially electrically conductive at room temperature but non-conductive or a vapor at lamp operating temperatures. Such an approach is disclosed in U.S. Patent No. 5,670,842 (Dolan, et al.).

5 Fig. 1 illustrates a typical configuration of an electrodeless lamp of the type with which the present invention is concerned. Specifically, a source or generator 16 generates microwave or RF energy and delivers the energy into a waveguide 18. The waveguide 18 directs the generated energy waves and couples the energy waves into a cavity 6, typically provided with a conductive mesh grid 8 for retaining the generated waves within the cavity 6 while allowing light waves to emanate therefrom. A  
10 transparent quartz bulb 10 in the cavity 6 is typically spherical or otherwise suitably configured and encloses a fill material containing sulfur and/or selenium, a trace amount of krypton-85 (e.g., 0.1 microcurie) and xenon gas and provides light when excited to form a plasma by the generated energy waves. The sulfur, selenium or  
15 sulfur/selenium mixture may be a solid having a low vapor pressure at room temperature and become gaseous with a high vapor pressure (e.g., two to twenty atmospheres) at typical lamp operating temperatures.

In operation, the radiation of the energy waves excites the fill atoms in the bulb 10 to effect a discharge of electrons. The discharged electrons collide with other fill  
20 atoms causing a further discharge of electrons, thereby increasing the total population of free electrons. The increased population of free electrons results in increased collisions and the process avalanches into radiation of light from a plasma. In the illustrated embodiment, the bulb 10 is connected by its elongate stem 12 to a motor 14 for rotating the bulb 10 about the longitudinal axis of the stem 12. In other  
25 embodiments, no mechanism for bulb rotation is required.

It is often necessary to restart or restrike the plasma ignition in a bulb as soon as possible after light discharge has been extinguished. Bulbs with fills of sulfur, selenium, a trace amount of krypton-85 and any quantity of xenon gas are difficult to start and difficult to restrike.

### 30 SUMMARY

The addition of a selected quantity (i.e., typically 50 torr or more partial pressure) of xenon provides lamps with a higher efficacy (about two to five percent

higher) as measured in lumens per watt as compared to a similar fill with a comparable partial pressure of argon. However, as noted above, it is difficult to start bulbs containing xenon, and there is a corresponding difficulty in restarting or restriking the bulb after it has been operating and has become hot. Thus, when using xenon bulb  
5 fills, a significant time lag has been required before restriking, since the bulb must cool sufficiently to reduce internal pressure before restarting or restriking is possible.

It is an object of the present invention to provide an inexpensive and reliable bulb fill for enhancing ignition in electrodeless lamps without the use of additional circuitry.

10 According to the invention, an improved starting capability and/or a reduced restrike time can be obtained in discharge lamps, particularly, but not necessarily, lamps having sulfur and / or selenium fill with added xenon, by adding a surprisingly small amount (e.g. relatively low partial pressure) of argon gas into the bulb fill. Moreover, the fill of the present invention only minimally affects lamp efficacy (as  
15 measured in lumens per watt).

It is another object of the present invention to provide an additive to the primary fill in high efficacy electrodeless lamps for greatly enhancing the starting, ignition and restrike capability of the lamp.

It is yet another object of the present invention to greatly enhance the starting  
20 and restrike capability of the high efficacy lamp including the sulfur/selenium/xenon fill mixture which has been demonstrated to provide a high efficacy but also a high difficulty in starting.

The above objects are achieved individually and in combination, and it is not intended that the present invention be construed as requiring two or more of the  
25 objects to be combined unless expressly required by the claims attached hereto.

In one embodiment of the invention, a lamp bulb for a discharge lamp includes a light transmissive envelope and a fill disposed in the envelope. The fill has the characteristic of emitting light when excited by high frequency electrical energy. The fill includes a first component principally for emitting light, a second component having  
30 a selected fill pressure and a third component having a selected fill pressure, wherein the selected fill pressure of the second component is substantially greater than the selected fill pressure of the third component, and wherein the presence of the third component in the fill at its respective selected fill pressure causes a disproportionately

large reduction in a breakdown strength of the fill. The first component may include, for example, sulfur, selenium or a mixture of sulfur and selenium. The second component includes either xenon or krypton, preferably at a partial pressure in the range of about 50 to 200 torr. The third component includes either argon, neon, or helium at a lower partial pressure, preferably in the range of about 5 to 20 torr. The fill may also include a trace amount of a radioactive material, krypton-85, typically about 0.1 micro curies.

The above and still further objects, features and advantages of the present invention will become apparent upon consideration of the following detailed description of specific embodiments thereof, particularly when taken in conjunction with the accompanying drawing.

### **BRIEF DESCRIPTION OF THE DRAWING**

Fig. 1 is a block diagram of an electrodeless lamp having a bulb enclosing a fill material.

### **DESCRIPTION**

A necessary (but not sufficient) condition for igniting a discharge in a gas subjected to an electric field is that each free electron generates at least one other free electron before recombining and being lost to the discharge. The free electron density can then increase until reaching some limiting value. This phenomena is known as "Townsend Avalanche". One measure of the breakdown strength of a gas is the probability per unit path length that an electron will produce another free electron. This probability coefficient is a function of the electric field strength, the type of gas, and the gas density; therefore it is known that for electric field strengths and fill pressures typically used in an electrodeless lamp, argon has a higher probability coefficient than xenon. The probability coefficient for a mixture of gases should be, using conventional wisdom, something intermediate the values for each gas separately.

Thus, relying on the teachings of the prior art, one would expect that for each gas, the number of ionizing collisions should be proportional to the number of gas atoms and that the probability coefficient should vary linearly with gas mixture composition. For example, a mixture dominated by xenon should have breakdown

characteristics similar to pure xenon and should show a gradual decline in breakdown strength as argon is added.

In accordance with the present invention, and surprisingly, an unexpectedly small addition of argon causes a disproportionately large reduction in breakdown strength in the sulfur / selenium/ xenon bulb fill and allows more reliable and effective starting and quicker restrikes without a significant impact on efficacy. This highly advantageous result is not to be expected from study of the prior art.

Exemplary fill mixtures of xenon and argon include a broad range of selected quantities of xenon gas and argon gas. In the preferred embodiment, about 5 torr of argon is used with a selected fill pressure of xenon (e.g., a partial pressure of 100 torr or more) to provide both high reliability and high efficacy.

According to one embodiment of the present invention, more rapid and reliable ignition in the bulb 10 of Fig. 1 is accomplished by providing a fill within the bulb 10 including a first fill component (e.g., sulfur, selenium, or a mixture of sulfur and selenium), a second fill component (preferably xenon gas) at a selected fill pressure and a third component (preferably argon gas) at a selected fill pressure significantly less than the fill pressure of the second fill component. As noted above, the fill may also include a trace amount of a radioactive material, krypton-85, typically about 0.1 micro curies.

Ferro-resonant power supplies produce higher peak powers which are useful in lamp starting. Switching power supplies are less expensive, smaller and lighter but do not provide the high peak power output. The use of a switching power supply exacerbates problems with starting and restriking since lamps are typically more difficult to start at lower voltages. Thus, the improved starting and restriking characteristics of the fill of the present invention is especially well suited for use in lamps having modern switching power supplies.

For illustration and comparison purposes, Tables 1-3 below list starting data for various embodiments of the invention. In each case, the same test bed was used. The bulb included a mixture of sulfur and selenium is provided in the same amount to provide a desirable color characteristic. The test bed included a switching power supply operating with a line voltage of 208V. Each bulb was energized by the source and the number of starts was recorded for the indicated quantity of bulbs. A given

bulb is considered to start reliably if successful ignition was observed in every attempt for a selected number (usually five to ten) of attempts.

For each set of data, a bulb including 50 torr of xenon and no argon is provided as a baseline. A bulb with this fill generally started, although not always. Bulbs with higher pressures of xenon (e.g. 100, 150, or 200 torr) were not used as a baseline because at these higher pressures it is generally known that the bulb will not start reliably.

**Table 1**

Gas Xe	Mix Ar	# of Bulbs Starting Reliably	Normalized LPW
50	0	2/3	1.000
50	5	3/3	0.996
100	5	2/3	1.014
200	5	2/3	1.021

**Table 2**

Gas Xe	Mix Ar	# of Bulbs Starting Reliably	Normalized LPW
50	0	5/5	-
50	10	3/3	-
100	10	2/3	-
150	10	2/3	-

**Table 3**

Gas Xe	Mix Ar	# of Bulbs Starting Reliably	Normalized LPW
50	0	3/4	1.000
100	20	0/2	1.020
200	20	0/2	1.028

10 Similar results with a line voltage of 230 V are listed in Table 4:

**Table 4**

Gas Xe	Mix Ar	# of Bulbs Starting Reliably	Normalized LPW
50	0	0/1	1.000
50	10	1/1	0.982
100	10	1/1	0.997
150	10	0/1	1.022



Another aspect of the invention relates to measured restrike time for an extinguished lamp at near operating temperature (i.e., a hot bulb). Restrike time averaged 4.5 minutes for 50 torr Xenon bulbs and averaged 2.75 minutes for 50 torr Xenon / 5 torr Argon bulbs (with a reflector attached and at 25°C ambient temperature). Thus, the addition of 5 torr of Argon to the 50 torr Xenon lamp fill significantly reduced restrike time by an average of 1.75 minutes.

As can be seen from the above tables, bulb fills with higher pressures of xenon yield higher efficacies but are harder to start. The addition of low partial pressures of argon (e.g., about 5 torr) or a similar noble gas (e.g. neon or helium) aids in starting with only a small effect on lamp efficacy. Notably, this benefit extends to the reliable starting of very high pressure xenon (i.e. 100 torr or more) which would not otherwise be practical. Also, as noted above, the addition of low partial pressures of argon significantly reduces the restrike time.

It will be appreciated that the embodiments described above and illustrated in the drawing represent only a few of the many ways of implementing the efficient and easily started lamp of the present invention. Specifically, while the invention has been described with respect to a microwave excited electrodeless sulfur / selenium lamp, it is expected that the benefits of the invention are equally applicable to other fill components (e.g. mercury and metal halides), RF lamps (e.g. inductive and capacitive), and electroded lamps.

Having described preferred embodiments of a new and improved method and apparatus it is believed that other modifications, variations and changes will be suggested to those skilled in the art in view of the teaching set forth herein. It is therefore to be understood that all such variations, modifications and changes are believed to fall within the scope of the present invention as defined by the appended claims.

## CLAIMS

What is claimed is:

- 1           1)     A lamp bulb for a discharge lamp, comprising:  
2               a light transmissive envelope; and  
3               a fill disposed in the envelope, the fill having the characteristic of emitting light  
4 when excited by high frequency electrical energy, the fill including a first component  
5 principally for emitting light, a second component having a selected fill pressure and a  
6 third component having a selected fill pressure,  
7               wherein the selected fill pressure of the second component is substantially  
8 greater than the selected fill pressure of the third component,  
9               and wherein the presence of the third component in the fill at its respective  
10 selected fill pressure causes a disproportionately large reduction in a breakdown  
11 strength of the fill.
  
- 1           2)     The lamp bulb as recited in claim 1, wherein the selected fill pressure of  
2 the second component is about 5 to 40 times greater than the selected fill pressure of  
3 the third component.
  
- 1           3)     The lamp bulb as recited in claim 1, wherein the selected fill pressure of  
2 the second component is a partial pressure in the range of about 50 to 200 torr.
  
- 1           4)     The lamp bulb as recited in claim 1, wherein the selected fill pressure of  
2 the third component is a partial pressure in the range of about 5 to 20 torr.
  
- 1           5)     The lamp bulb as recited in claim 4, wherein the selected fill pressure of  
2 the third component is a partial pressure of about 5 torr.
  
- 1           6)     The lamp bulb as recited in claim 1, wherein the first component  
2 pressure includes at least one member selected from the group of sulfur and  
3 selenium, the second component is one member selected from the group of xenon

4 and krypton, and the third component is one member selected from the group of  
5 argon, neon, and helium.

1 7) A lamp bulb for a discharge lamp, comprising:  
2 a light transmissive envelope; and  
3 a fill disposed in the envelope, the fill having the characteristic of emitting light  
4 when ignited and excited by high frequency electrical energy and including a first  
5 component principally for emitting light, a second component selected from the group  
6 of xenon and krypton at a partial pressure in the range of about 50 to 200 torr, and a  
7 third component selected from the group of argon, neon, and helium at a partial  
8 pressure in the range of about 5-20 torr.

1 8) The lamp bulb as recited in claim 7, wherein the presence of the third  
2 component in the fill causes a disproportionately large reduction in the breakdown  
3 strength of the fill.

1 9) A discharge lamp, comprising:  
2 a source of high frequency energy;  
3 a light transmissive envelope;  
4 a fill disposed in the envelope, the fill having the characteristic of emitting light  
5 when excited by high frequency electrical energy, the fill including a first component  
6 principally for emitting light, a second component having a selected fill pressure and a  
7 third component having a selected fill pressure; and  
8 means for coupling the high frequency energy to the fill,  
9 wherein the selected fill pressure of the second component is substantially  
10 greater than the selected fill pressure of the third component,  
11 and wherein the presence of the third component in the fill at its respective  
12 selected fill pressure causes a disproportionately large reduction in a breakdown  
13 strength of the fill.

1           10)    A method for improving starting characteristics in a discharge lamp  
2   having a bulb enclosing a fill including a first component principally for emitting light  
3   and a second component selected from the group of xenon and krypton having a  
4   selected fill pressure, the method including the step of:  
5           adding a third component selected from the group of argon, neon, and helium  
6   at a selected pressure substantially less than the selected pressure of the second  
7   component.


1           11)    The method of claim 10, wherein the selected pressure of the second  
2   component is at a partial pressure in the range of about 50 to 200 torr and the  
3   selected pressure of the third component is at a partial pressure in the range of about  
4   5 to 20 torr.

1           12)    The method of claim 11, wherein the second component is xenon and  
2   the third component is argon.

1           13)    A method for reducing restrike time in a discharge lamp having a bulb  
2   enclosing a fill including a first component principally for emitting light and a second  
3   component selected from the group of xenon and krypton having a selected fill  
4   pressure, the method including the step of:  
5           adding a third component selected from the group of argon, neon, and helium  
6   at a selected pressure substantially less than the selected pressure of the second  
7   component.

1           14)    The method of claim 13, wherein the selected pressure of the second  
2   component is at a partial pressure in the range of about 50 to 200 torr and the  
3   selected pressure of the third component is at a partial pressure in the range of about  
4   5 to 20 torr.

1           15)    The method of claim 14, wherein the second component is xenon and  
2   the third component is argon.



# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US98/16822

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC(6) :B31F 1/07; B41F 15/00, 17/00, 17/08; B41L 13/00, 13/04 US CL :101/8, 25, 27, 35, 38.1, 40.1, 114, 116, 119, 120 According to International Patent Classification (IPC) or to both national classification and IPC														
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) U.S. : 101/8, 25, 27, 35, 38.1, 40.1, 114, 116, 119, 120 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched NONE Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) U.S. PTO APS SEARCH TERMS: "rotary(p)screen(p)print?(p)(bottles or cans or containers)(p)cylindrical"														
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>														
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.												
Y	US 5,471,924 A (HELLING) 05 December 1995 (05/12/95) See the entire document	1-41												
Y	US 4,628,857 A (CONINGSBY) 16 December 1986 (16/12/86) See the entire document	1-41												
Y	US 3,816,207 A (ROBERTSON ET AL.) 11 June, 1974 (11/06/74) See the entire document	12, 21, 30, 41												
A	US 4,091,726 A (WALKER) 30 May, 1978 (30/05/78) all	1-55												
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.														
<table border="0"> <tr> <td>* Special categories of cited documents:</td> <td>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>*A* document defining the general state of the art which is not considered to be of particular relevance</td> <td>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>*B* earlier document published on or after the international filing date</td> <td>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>*G* document member of the same patent family</td> </tr> <tr> <td>*O* document referring to an oral disclosure, use, exhibition or other means</td> <td></td> </tr> <tr> <td>*P* document published prior to the international filing date but later than the priority date claimed</td> <td></td> </tr> </table>			* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	*B* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family	*O* document referring to an oral disclosure, use, exhibition or other means		*P* document published prior to the international filing date but later than the priority date claimed	
* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention													
*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone													
*B* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art													
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family													
*O* document referring to an oral disclosure, use, exhibition or other means														
*P* document published prior to the international filing date but later than the priority date claimed														
Date of the actual completion of the international search 09 DECEMBER 1998		Date of mailing of the international search report 14 JAN 1999												
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer REN YAN Telephone No. (703) 308-0978												